


Client:

Product description: agglomerated cork stoppers made from cork granules mixed with glue to ensure filling of bottle and preserve its content.

Product details	<p>Agglomerated cork stoppers in 38x23mm. Corks peroxide washed (H₂O₂ 130V), ink printed, treated to improve sealing and mechanical performances. Corks packed in sealed plastic bags / cardboard cartons.</p>
------------------------	--



Technical details	Dimensions / Tolerances
Visual	refer to grade (±)
Cork dimensions – length	(B) ± 0,5mm
Cork dimensions – diameter	(A) ± 0,3mm
Moisture content	4-9%
Solid residues	Below 2mg/cork
Peroxide residues	Below 0,2mg/cork
Sensorial	Negative
Shear Strength	≥ 6 daN
Tortion angle	≥ 35°
TCA	≤ 3,0 ppt

Storage / Use Conditions
<ul style="list-style-type: none"> - Corks to be stored in a dry and ventilated place - Protected from direct sun light, heat, offensive smells, where there are no chlorine or halogenated products - Temperature between 15°C and 20°C - Moisture Environment between 40 and 70% - Cork stoppers should be used within 120 days after loading - Cork stoppers ready for bottling, should not be moistened or heated prior use - Open bags just for use - Filling level, to be kept at least at 15mm from cork bottom - Bottles should be stored upright position